



Ultra Flat Ceiling White



Interior



Tintable



Water Wash Up

Description

Evolving Elements Ultra Flat Ceiling White is a high quality, water based, high cover ceiling flat finish having minimal odour, suitable for use in living areas with high illumination. Evolving Elements Ceiling White dries to a flat finish. Designed to provide high opacity cover on all living area ceilings. It is easy to apply, non-yellowing, quick drying and excellent for hiding surface imperfections. It contains anti fungicidal additives and may be tinted to a select range of colours. It is environmentally friendly, non-toxic, non-hazardous and non-flammable.

Attributes

- Smooth, flat finish
- Superior covering power
- Hides surface imperfections
- Low VOC
- Low roller spatter
- Low odour

Areas of Application

Plasterboard ceilings, concrete, plaster, cement render, timber and hardboard. For interior only on pre-primed and pre-painted substrates. This product is not recommended for use on walls.

Colours

Primarily White. Can be tinted to a select colour range. Dries to Flat finish

Before Painting

Read safety information below before painting.

- Sound preparation is the key to a perfect finish.
- The surface must be clean, dry and free of dirt, dust, grease and grime.

- Glossy surfaces should be sanded to remove gloss before painting.
- Remove old, loose or flaking paint.
- Repair all damaged areas and sand smooth.
- If mould is present, it must be completely removed. Apply a solution of 1 part household bleach and 3 parts water.

Rinse thoroughly with clean water. Allow to dry.

- Seal new fresh plasterboard and bare absorbent surfaces with the appropriate JPS Coatings preparatory coat prior to painting.

Application & After Painting

- Apply when the air and surface temperatures are above 10°C and below 35°C.
- Stir contents before use with a broad paddle to ensure paint is thoroughly mixed.
- Check your colour is correct, as tinted paint is not refundable.
- When more than one container of the same colour is required, intermix containers to ensure colour uniformity. If you feel that you may run out of paint, stop at a natural break.
- Apply 2 full, even coats using a synthetic brush, roller, or spray.
- Apply liberally, working from dry areas into the paint's wet edge and finish with gentle strokes along the complete section.
- Avoid excessive rolling or brushing.

After Painting

- Remove as much paint as possible from brushes and rollers before cleaning up in soapy water away from drains.
- Wipe up spills immediately with a damp cloth.

Flammability & Transport information

Non-flammable

Containers must be secured and stored upright during transit.

Containers must not be exposed to excessive heat or cold.

Properties & Performance Guide

Dry & Recoat Times	Touch Dry - 30 minutes / Recoat - 4 hours / Fully Cured - 7 days Figures are quoted at 25°C and at 50% humidity. Drying will take longer at lower temperatures or higher relative humidity.
Coverage per Coat	Up to 14 m ² /L depending on the surface texture, porosity and method of application.
Thinning	Thinning is generally not required. If necessary to aid spray atomisation and climate conditions, thin with up to 5% clean water.
Method of Application	Brush, Roller or Spray. Please use the method best suited to your requirement and skill. The use of a lamb's wool or synthetic sleeve of 10 - 12 mm nap on a flat surface is recommended. For airless spray application, optimum pressure of 2800 psi and nozzle size of 0.017-0.019 inches is suggested as a guideline.
Toxicity	Dry film is non toxic
Clean Up / Environmental	Clean up with cold water away from drains. Protect Our Environment: Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, and then disposed of via special waste collection services. Empty paint containers should be left open in a well-ventilated area to dry out. Disposal of empty paint containers may differ between local authorities. Refer to state / local EPA and council web sites for environmental and safe disposal details.
Packing size	Available in 4, 10 and 15 litre containers.

Usage Areas

Usage	Preparatory Coats
Previously Painted Surfaces	No sealer or undercoat is required on sound surfaces. Apply one coat of Evolving Elements WB Primer Sealer Undercoat to even porosity on patched surfaces, or to maximise opacity of the topcoat.
New Paper-Faced Plasterboard, Unpainted Brick, Cement Render, Fibre Cement or Masonry	Apply one coat of Evolving Elements WB Primer Sealer Undercoat
Bare Timber and MDF	Apply one coat of Evolving Elements WB Primer Sealer Undercoat. A second coat may be required on tannin rich hardwoods.
New Set Plaster	Apply one coat of Evolving Elements Binder Sealer

Safety Data



General First Aid Instructions	For advice, contact the Poisons Information Centre on 131 126 (Aust), 0800 764 766 (NZ) or a doctor. If swallowed, do not induce vomiting. Give a glass of water to drink. If in eyes, wash out immediately with water. If inhaled, remove from contaminated area to fresh air. If skin contact occurs, remove contaminated clothing and flush contaminated skin with water.
General Safety Directions	Keep out of reach of children. Avoid contact with skin and eyes. Avoid prolonged breathing of vapour. Wash hands thoroughly after use. PROVIDE ADEQUATE VENTILATION DURING USE.
Further Information	For the latest information refer to the Safety Data Sheet or contact JPS Coatings Customer Service on +61 3 9357 6644

This information is provided with respect to the listed JPS Coatings products;

(a) You review the Technical Data Sheets (TDS) and Safety Data Sheets (SDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by JPS Coatings; (c) the product be transported and handled in accordance with the SDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product. The information in the technical data sheet was prepared using information gathered during product development. While JPS Coatings endeavours to update this information and maintain the accuracy of its contents, JPS Coatings cannot guarantee that the information is wholly comprehensive. JPS Coatings recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact JPS Coatings Office. To the full extent permitted by law, JPS Coatings liability for breach of a condition or warranty implied into the contract for sale between JPS Coatings and you by law is limited at JPS Coatings election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product. The technical information and suggestions for use and application are given in good faith. Since conditions of use are beyond the manufacturer's control, information contained herein is without warranty, implied or otherwise. The manufacturer does not assume any liability for any loss or injury resulting from the use of the product. Cooler temperature, higher film thickness and higher humidity conditions will require longer drying times